

II. Specifications

Product Technical Parameters					
Category		Original Splicing Screen - SAMSUNG			
Size / Bezel		49 Inch/ 3.5 mm	46 Inch/ 1.8 mm	55 Inch/ 3.5 mm	55 Inch/ 1.8 mm
Series Number		SDDID46SMP35	SDDID46SMP18	SDDID55SMP35	SDDID55SMP18
LCD Panel	Screen Size	46"	46"	55"	55"
	LCD Type	TFT-LCD	TFT-LCD	TFT-LCD	TFT-LCD
	Display Size (mm)	1018.08*572.67	1018.08*572.67	1209.6*680.4	1209.6*680.4
	Overall Dimension (mm)	1021.98*576.57	1020.02* 574.61	1213.5*684.3	1211.54*682.34
	Resolution	1920*1080	1920*1080	1920*1080	1920*1080
	Bezel	3.5 mm	1.8 mm	3.5 mm	1.8 mm
	Brightness	500/700 cd/ m ²	500/700 cd/ m ²	500/700 cd/ m ²	500/700 cd/ m ²
	Contrast Ratio	3000:1	4000:1	4000:1	4000:1
	Response Time	6ms	6ms	6ms	6ms
	Service Life (min.)	60,000 hrs	60,000 hrs	60,000 hrs	60,000 hrs
	Display Colors	16.7	16.7	16.7	16.7
Electrical Power	Power Supply	AC100 V ~ 240 V, 50-60 Hz	AC100 V ~ 240 V, 50-60 Hz	AC100 V ~ 240 V, 50-60 Hz	AC100 V ~ 240 V, 50-60 Hz
Consumption	Power Consumption	≤200W	≤200W	≤280W	≤280W
	Standby Power	≤3W	≤3W	≤3W	≤3W
Weight	Net Weight	25Kg	25Kg	30Kg	30Kg
Features	Menu Language	Chinese, English			
	3D Comb Filtering	Yes			
	Digital Noise Reduction	TNR			
	Heat Dissipation	Built in industrial fan, intelligent temperature control system.			
	Video Format	PAL/NTSC /SECAM			
Other	Operating Temperature:	0°C ~ 50°C			
	Working Humidity	20% ~ 80%			